FLIA

INFORMATION REPORT INFORMATION REPORT

CENTRAL INTELLIGENCE AGENCY

This material contains information affecting the National Defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C. Secs. 793 and 794, the transmission or revelation of which in any manner to an unauthorized person is prohibited by law.

C-O-N-F-I-D-E-N-T-I-A-L 50X1 COUNTRY USSR (Moscow Oblast) REPORT NO. SUBJECT Coal Unloading and Storage Area DATE DISTR. at Moskva Tovarnaya 5 NO. OF PAGES DATE OF INFO. REQUIREMENT NO. RD · 50X1 PLACE ACQUIRED REFERENCES DATE ACQUIRED Έ. 50X1 50X1

C-O-N-F-I-D-E-N-T-I-A-L


50X1

50X1

	, ,,		1 //				- 77								
STATE	#x	ARMY	#x	NAVY	#x	AIR .	# x	Fi	31 #	AEC	1				
					,,		(Not	e. W	ashingtor	distribution	n Indicate	d by "X"	'. Field c	distribution b	y "#".)

INFORMATION REPORT INFORMATION REPORT

Declassified in Part - Sanitized Copy Approved for Release @ 50-Yr 2013/05/30 : CIA-RDP82-00046R000500090001-6 CONFIDENTIAL REPORT NO. 50X1 50X1 USSR (Moscow Oblast) COUNTRY DATE DISTR. 25 April 1955 Coal Unloading and Storage Area at Moskva SUBJECT NO. OF PAGES 4 50X1 DATE OF INFORMATION REFERENCES: PLACE ACQUIRED THIS IS UNEVALUATED INFORMATION 50X1 SOURCE From January to September - October 1948, GOREM No. 11 constructed a new coal unloading and storage area at Moskva Tovarnaya which is the freight terminal yard for the Moscow-Donbas Railroad located in the southern part of the city of Moscow. 2. Most of the coal shipped to this installation was mined in the Moscow area (podmoskovskiy ugol') but there were also shipments of Donbas The coal was loaded from bunkers into trucks and then delivered to various consumers in Moscow. None of the coal was retained for railroad use. All of the metal ties which were used for construction of the installation consisted of war booty from Germany. Following is a legend of the coal unloading and storage area on page 3. Numbers in parentheses refer to numbers indicated on the sketch. A 1.2-meter-high fence made of metal ties surrounding the entire installation. The area enclosed by the fence was approximately 100 meters by 200 meters. (2) A ramp for unloading railroad coal cars. It was constructed of metal ties and was filled in with sand. The ramp could handle about twelve 50 - 60 ton coal cars at one time and it stood about 2.2 meters above the ground. Two men, one on each side of the train, could empty the cars in about 15 minutes. The floors of each coal car consisted of eight hatches, four on each side. When the hatches were opened manually, the coal spilled out on both sides of the ramp. (See memory sketch of the ramp and of the unloading hatches of a freight car on page 4). CONFIDENTIAL



- (3) Two open storage areas about 20 meters wide, which stored coal unloaded from railroad cars. The areas were surfaced with a floor of metal ties.
- (4) Two spur tracks. A steam-operated crane equipped with a boom and clamshell bucket and mounted on railroad wheels transferred coal from the open storage area (3) to the bunkers (5).
- (5) Four metal bunkers for storing and for loading coal into trucks (see sketch on page 4).
- (6) Two stone and concrete aprons for trucks.
- (7) Four truck entrances.

Comment: GOREM (Golovnoy Remontno - Vostanovitelniy Poyezd) No. 11 was a forward repair and reconstruction train.

50X1

50X1


CONFIDENTIAL

CONFIDENTIAL -3-

50X1

50X1

Sketch of Coal Unloading and Storage Area at Moskva Tovarnava



Unloading Ramp and Coal Cars

